# 1.- Product name:

SLEEVE

#### 2.- Name and address of the manufacturer

NOXIFER S.L. Ctra de Sarral a Barberà, parcel·la 21 43424 - SARRAL (Tarragona) - España

## 3.- Expected use:

Steel channel embbedded in the concrete. Inside of the sleeve, are inserted the rebars of the precast pilar or the tendons used in prestressed concrete. The sleeve has a ribbed profile in order to guarantee the connection with the concrete.

## 4.- System of assessment and verification of constancy of performance:

2+

#### 5.- Notified body:

APPLUS nº 0370 Factory Production Control Evaluation: System 2+ Factory production control certificate 0370 - CPR - 1685 of 7th of march 2014

## 6.- Performance features

Essential features	Performances		
Geometric Tolerances	UNE EN 523 - UNE EN 524		
Weldability	NPD		
Fracture toughness	NPD		
Reaction to fire	Classified material: Class A1		
Cadmium emission	NO EMISSIONS		
Radioactivity emission	NO EMISSIONS		
Durability	NPD		

Structural features	Performances	
Base material	DC01 or DX51D+Z	
Sizing	UNE EN 523 - UNE EN 524	
Fire resistance	NPD	
Fatigue resistance	NPD	
Bearing capacity	NPD	
•		

Technical specifications UNE EN 523 - UNE EN 524

The benefits of the product identified in point 1 are in accordance with those declared in point 6 This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2

Signed for and on behalf of the manufacturer by: Josep Rull, Managing Director

Sarral 30th of August 2022 Edition: 001